



161012050762

# 检测报告

报告编号: TKJC2021BA0983-2W

委托单位: 建大橡胶(中国)有限公司

检测类别: 委托检测

苏州泰坤检测技术有限公司

地址: 太仓市娄东街道北京东路88号东G

邮箱: sztk@sztaikun.com

邮编: 215400

电话: 0512-53867996





# 声 明

## Statement

1.本报告无报告专用章和批准人签章无效。

This report is invalid without the approver's signatures and special seal of inspection.

2.委托单位对报告检测结果如有异议，请于收到报告之日起十天内与本单位联系，逾期不予受理。

The applicant shall contact our company within 10 days after getting the results, if the applicant has any questions about the results. Overdue application will be dismissed.

3.委托单位对样品的代表性和资料的真实性负责，否则本单位不承担任何相关责任。

The applicant should undertake the responsibility for the provided samples' representativeness and document authenticity. Otherwise, our company has not relevant responsibilities.

4. 本报告仅对所测样品负责，报告数据仅反映对所测样品的评价，对于报告及所载内容的使用、使用所产生的直接或间接损失及一切法律后果，本单位不承担任何经济和法律后果。

This report is only responsible for the provided sample. The test results only represent the evaluation of the tested sample. Our company will not be responsible for any economical or legal liability generated from direct or indirect usage of the test report.

5.除委托单位特别申明并支付样品管理费，所有样品超过标准规定的时效期本单位均不再留样。

Only if the applicant makes particular statement and pays the management fee of the test samples, will the rest testing samples not be kept after expiration date the standard provisions regulated.

6.本报告全部或部分复制、涂改或以其它任何形式篡改的均属无效。

Any unauthorized fully or partially copy of this report, alteration and any other falsifications shall be invalid.




7.本单位保证检测工作的客观公正性，对委托单位的商业信息、技术文件等商业秘密履行保密义务。

Our company assures objectivity and impartiality of the test, and fulfills the obligation of confidentiality for applicant's commercial information, and technique document.

# 检测报告

共 2 页 第 1 页

受检单位	建大橡胶（中国）有限公司		
地址	昆山市昆嘉路2号		
联系人	雷雄兵	联系电话	13962438492
样品类别	废水	采样人	陆惠峰、顾健
采样日期	2021.06.30	分析日期	2021.06.30 ~ 2021.07.07
检测目的	为建大橡胶（中国）有限公司提供检测数据		
检测内容	pH 值、化学需氧量、氨氮、悬浮物、生化需氧量、石油类、动植物油、阴离子表面活性剂、色度		
检测依据及方法	见附表 1		
主要检测仪器设备	见附表 2		
检测结果	见第 2 页		
备注	本次检测时段内：总务课生活污水排放口（接市政污水官网提升井）WS-K-43501 所测 pH 值、化学需氧量、氨氮、悬浮物、色度、生化需氧量、石油类、动植物油、阴离子表面活性剂浓度均符合《污水排入城镇下水道水质标准》（GB/T 31962-2015）表 1 B 级标准限值要求。		

编制人:   
 审核人:   
 签发人: 

编制日期: 2021年07月08日  
 审核日期: 2021年07月08日  
 签发日期: 2021年07月08日



## 检测结果

表 1: 废水检测结果统计表

单位: pH 值无量纲, 色度为倍, 其余为 mg/L

样品编号及 样品名称	采样时间	样品性状			检测项目								
		颜色	气味	性状	pH 值	化学需 氧量	氨氮	悬浮物	色度	生化需 氧量	石油类	动植物 油	阴离子 表面活性 剂
BA0983-0630F2-1 总务课生活污水排放口 (接市政污水官网提升井) WS-K-43501	2021.06.30 13:15	微黑	弱	微浑	7.7	247	39.3	125	16	125	3.80	1.55	0.39
BA0983-0630F2-2 总务课生活污水排放口 (接市政污水官网提升井) WS-K-43501	2021.06.30 13:45	微黑	弱	微浑	7.5	254	41.5	117	16	120	3.46	1.43	0.41
BA0983-0630F2-3 总务课生活污水排放口 (接市政污水官网提升井) WS-K-43501	2021.06.30 14:15	微黑	弱	微浑	7.4	237	37.8	120	16	112	3.62	1.55	0.38
BA0983-0630F2-4 总务课生活污水排放口 (接市政污水官网提升井) WS-K-43501	2021.06.30 14:45	微黑	弱	微浑	7.8	242	38.3	110	16	117	3.27	1.48	0.39
均值					7.4~7.8	245	39.2	118	16	119	3.54	1.50	0.39
《污水排入城镇下水道水质标准》 (GB/T 31962-2015) 表 1 B 级					6.5~9.5	500	45	400	64	350	15	100	20
备注: 所列标准由客户提供。													



## 检测结果

附表 1: 检测依据及方法

检测类别	检测项目	分析方法
废水	pH 值	水质 pH 值的测定 电极法 HJ 1147-2020
	化学需氧量	水质 化学需氧量的测定 重铬酸盐法 HJ 828-2017
	氨氮	水质 氨氮的测定 纳氏试剂分光光度法 HJ 535-2009
	悬浮物	水质 悬浮物的测定 重量法 GB/T 11901-1989
	生化需氧量	水质 五日生化需氧量(BOD <sub>5</sub> )的测定 稀释与接种法 HJ 505-2009
	石油类、动植物油	水质 石油类和动植物油的测定 红外分光光度法 HJ 637-2018
	阴离子表面活性剂	水质 阴离子表面活性剂的测定 亚甲蓝分光光度法 GB/T 7494-1987
	色度	水质 色度的测定 GB/T 11903-1989 稀释倍数法

## 检测结果

附表 2: 主要检测仪器设备

仪器型号、名称	仪器编号
SX811 便携式 ph 计	200111
Titrette50ml 数显滴定器	103001、103003
N2 可见分光光度计	100701
UV-1800 紫外可见分光光度计	100703
LE104E/02 电子天平	100105
GZX-9140MBE 电热鼓风干燥箱 (烘箱)	100502
JPSJ-605F 溶解氧测定仪	100301
SPX-250B-Z 生化培养箱	100302
OIL480 红外分光测油仪	100901

\* \* \* \* 报告结束 \* \* \* \*